

RK

RK Mangetrådet, fleksibel koblingskabel 450/750V

Application

Fleksibel kabel brukes for bruk til montering på innsiden av bygninger og for midlertidige bruk i friluft.



Specifications

Test voltage 2,5 [kV]



For halogenfri og flammehemmet, se RQ



Core (mm ²)	O.D. (mm)	Weight (kg/km)	P-no.
			Black / White / Red / Blu / G/G / Grey / Brown
1.2	3,0	20	1049937 / 1049946 / 1049939 / 1049944 / 1049941 / 1049942 / 1049943
2.5	3,7	30	1049950 / 1049959 / 1049952 / 1049953 / 1049954 / 1049955 / 1049956
4	4,2	45	1049960 / 1049961 / - / 1049962 / 1049963 / - / 1049964
6	4,8	65	1049970 / 1049971 / 1049972 / 1049973 / 1049974 / - / 1049975
10	6,3	120	1049976 / 1049977 / - / 1049976 / 1049976 / - / 1049976
16	7,4	170	1049983 / 1049984 / 1049985 / 1049986 / 1049987 / - / 1049988
25	9,1	260	1049989 / 1049990 / - / - / - / 1049991 / -
35	10,7	360	1049992 / - / - / - / 1049993 / - / -
50	12,7	520	1049994 / - / - / - / 1049995 / - / -
70	14,8	740	1049996 / - / - / - / 1049998 / - / -
95	17,0	960	1049998 / - / - / - / 1049999 / - / -