

PFSK

Skjermet, fleksibel multikabel. $n \times (0.22 - 0.50)\text{mm}^2$

Application

Skjermet, fleksibel kabel for signal-, data- og lydanlegg. De fortinnede lederene gir kabelen gode loddeegenskaper.



Construction

Conductor	0.22 [mm ²] 7 x 0,20 [mm]
Screen	85 [% optical coverage]

Specifications

Operating temperature	-5 to +80 [°C]
Temperature @ installation	0 to +70 [°C]
Capacitance betw. conductors	0.22 mm ² : 100 pF/100m, 0.50 mm ² : 105 pF/100m
Insulation resistance	100 [MΩ x km]
Min. bending radius	8 [x outer diam]



Kan erstatte LiYCY For uskjermet type, se PFK

Core (mm ²)	O.D. (mm)	Weight (kg/km)	P-no.
			100 m / 500 m
4 x 0.22	4,4	34	1032430 / 1032431
6 x 0.22	5,4	50	1032432 / 1032433
8 x 0.22	5,8	57	1032434 / 1032435
12 x 0.22	6,8	77	1032436 / 1032437
18 x 0.22	8,0	106	1032438 / 1032439
25 x 0.22	9,4	138	1032440 / -
36 x 0.22	10,8	195	- / 1032442
2 x 0.50	6,0	49	1032445 / 1032446
3 x 0.50	6,4	61	1032447 / -
4 x 0.50	7,0	71	1032448 / 1032450 / 1032449 (305m t&k)
6 x 0.50	8,0	98	1032451 / 1032452
8 x 0.50	8,5	110	1032453 / 1032454
12 x 0.50	10,1	160	1032455 / 1032456
18 x 0.50	11,6	232	1032457 / 1032458
25 x 0.50	13,9	290	1032459 / 1032460
36 x 0.50	16,1	410	1032461 Trm250m