

## RF-LLX-CL 7/8" 50

### Coupling Leaky Cable

50Ω

SHF1

DNV


### Application

Radiating coaxial cable for tunnels, ships, buildings and other closed areas.



### Construction coaxial

Conductor	Smooth Cu-tube $\varnothing = 9.0 \pm 0.2$ [mm]
Dielectric	Foamed PE $\varnothing = 22.0 \pm 0.5$ [mm]
Screen	Corrugated slotted Cu-tube $\varnothing = 24.9 \pm 0.5$ [mm]
Jacket	Black or grey SHF1
Outer diam.	$28.0 \pm 0.5$ [mm]
Jacket marking	NEK Kabel – RF-LLX-CL 7/8" 50 – SHF1 – DD.MM.YYYY – ****m



### Specifications Coax Cable

Temperature range	-25 – +70 [°C]
Impedance	50 [Ω]
Insulation resistance	10000 [MΩ/km]
Velocity factor	88 %
Max pulling force	1500 [N]
Min bending radius installed	140 [mm]
Min. bending flexible	250 [mm]

## Norms

Halogenfree, max content corrosive and toxic gases	IEC 60754-1 & IEC 60754-2
Material properties, insulation and sheath	IEC 60092-360 (359) 3582
Design and testing standards	IEC 60096-0-1 Ed 3 EN 50288-1
Flame resistance	IEC 60332-3-22 Cat.A
Flame retardant	IEC 60332-1-2
Smoke emission	IEC 61034-2
Oil and fuel resistant	IEC 60811-2-1 Mineral Oils, IRM 902: 23°C / 7 days, 70°C / 4h Diesel, IRM 903: 23°C / 7 days, 70°C / 4h
UV-resistant	ASTM G 154
Certification	DNV
Part No.	1092480



NEK offers connectors for RF-LLX-CL 7/8" 50:  
Female part no. 65444

## Attenuation

Frequency [MHz]	Attenuation [dB/100m ±5%]	Coupling loss 95% [dB±10%]
150	≤ 1.8	66
450	≤ 3.6	72
900	≤ 5.3	74
1800	≤ 7.6	80
2200	≤ 8.6	77
2400	≤ 9.0	78

## VSWR

Frequency [MHz]	-
260 – 480	≤ 1.25
820 – 960	≤ 1.25
1700 – 1860	≤ 1.25
1900 – 2050	≤ 1.30
2100 – 2200	≤ 1.30
2300 – 2400	≤ 1.30

## Updated

Date	Rev.	Description
21.10.2019	1	O.diam. and coupling loss
15.05.2020	2	VSWR
17.02.2022	3	Coupling loss
23.11.2023	4	Additional info